

EPIREZ EPOXY ANTI-SLIP FLOORING AGGREGATE [SIL-CARB]

Chemwatch Material Safety Data Sheet
Issue Date: 26-Apr-2006
C317SC

CHEMWATCH 8013-72
CD 2006/2 Page 1 of 8

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

EPIREZ EPOXY ANTI-SLIP FLOORING AGGREGATE [SIL-CARB]

SYNONYMS

"Product Code: E992712", carborundum, "silicon carbide", aggregate

PRODUCT USE

Aggregate for non-slip finish.

SUPPLIER

Company: ITW Polymers & Fluids
Address:
100 Hassall Street
Wetherill Park
NSW, 2164
AUS
Telephone: +61 2 9757 8800
Emergency Tel: +61 2 9757 8800
Fax: 1800 803 596

QUEENSLAND DISTRIBUTOR

INTERNATIONAL TRADERS Pty Ltd
6/286 Evans Rd
Salisbury - BRISBANE - QLD 4107
Phone (07) 3272 9051 Fax (07) 3272 9744

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

None under normal operating conditions.

SAFETY

Do not breathe dust.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
silicon carbide	409-21-2.	100

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons

continued...

EPIREZ EPOXY ANTI-SLIP FLOORING AGGREGATE [SIL-CARB]

Chemwatch Material Safety Data Sheet
Issue Date: 26-Apr-2006
C317SC

CHEMWATCH 8013-72
CD 2006/2 Page 2 of 8
Section 4 - FIRST AID MEASURES

Information Centre or a doctor.

EYE

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
 - Not considered a significant fire risk, however containers may burn.
- May emit corrosive fumes.

FIRE INCOMPATIBILITY

None known.

HAZCHEM

None

continued...

EPIREZ EPOXY ANTI-SLIP FLOORING AGGREGATE [SIL-CARB]

Chemwatch Material Safety Data Sheet
Issue Date: 26-Apr-2006
C317SC

CHEMWATCH 8013-72
CD 2006/2 Page 3 of 8

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing dust and contact with skin and eyes.
- Wear protective clothing, gloves, safety glasses and dust respirator.
- Use dry clean up procedures and avoid generating dust.
- Sweep up, shovel up or
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place spilled material in clean, dry, sealable, labelled container.

MAJOR SPILLS

Moderate hazard.

- CAUTION: Advise personnel in area.
- Alert Emergency Services and tell them location and nature of hazard.
- Control personal contact by wearing protective clothing.
- Prevent, by any means available, spillage from entering drains or water courses.
- Recover product wherever possible.
- IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.
- ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise Emergency Services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

silicon carbide 250 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

silicon carbide 50 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

silicon carbide 30 mg/m³

The threshold concentration below which most people will experience no appreciable risk of health effects:

silicon carbide 15 mg/m³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		

continued...

EPIREZ EPOXY ANTI-SLIP FLOORING AGGREGATE [SIL-CARB]

Chemwatch Material Safety Data Sheet
Issue Date: 26-Apr-2006
C317SC

CHEMWATCH 8013-72
CD 2006/2 Page 4 of 8

Section 6 - ACCIDENTAL RELEASE MEASURES

else $\geq 10\%$
where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

Multi ply paper bag with sealed plastic liner or heavy gauge plastic bag
NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse. Check that all containers are clearly labelled and free from leaks. Packing as recommended by manufacturer.

STORAGE INCOMPATIBILITY

None known.

STORAGE REQUIREMENTS

Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	Peak ppm	Peak mg/m3
Australia Exposure Standards	silicon carbide		10				

The following materials had no OELs on our record under the following CAS or Chemwatch (CW) numbers
Epirez Epoxy Anti-Slip Flooring Aggregate [Sil-Carb]: No data available for CW:8013-72

continued...

EPIREZ EPOXY ANTI-SLIP FLOORING AGGREGATE [SIL-CARB]

Chemwatch Material Safety Data Sheet
Issue Date: 26-Apr-2006
C317SC

CHEMWATCH 8013-72
CD 2006/2 Page 5 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

None assigned. Refer to individual constituents.

INGREDIENT DATA

SILICON CARBIDE:

Epidemiological evidence has demonstrated little potential for adverse effects on the lungs following occupational exposure to silicon carbide. No significant organic disease has developed where exposure has been controlled. Local exhaust ventilation proves to be effective in reducing exposures during silicon carbide grinding and machining.

Exposure at or below the TLV-TWA is thought to protect workers from the significant risk of material health impairment in the form of physical irritation. The OSHA-PEL TWA highlights the need to monitor the environment for respirable particles.

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- Barrier cream
- Eyewash unit.

ENGINEERING CONTROLS

- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
 - (a): particle dust respirators, if necessary, combined with an absorption cartridge;
 - (b): filter respirators with absorption cartridge or canister of the right type;
 - (c): fresh-air hoods or masks

continued...

EPIREZ EPOXY ANTI-SLIP FLOORING AGGREGATE [SIL-CARB]

Chemwatch Material Safety Data Sheet
Issue Date: 26-Apr-2006
C317SC

CHEMWATCH 8013-72
CD 2006/2 Page 6 of 8

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Solid; insoluble in water.

PHYSICAL PROPERTIES

Solid.

Does not mix with water.

Sinks in water.

Molecular Weight: Not applicable

Melting Range (°C): Not available

Solubility in water (g/L): Immiscible

pH (1 % solution): Not available

Volatile Component (%vol): Not available

Relative Vapour Density (air-1): Not applicable

Lower Explosive Limit (%): Not applicable

Autoignition Temp (°C): Not available

State: Divided solid

Boiling Range (°C): Not available

Specific Gravity (water-1): 3.2

pH (as supplied): Not available

Vapour Pressure (kPa): Not available

Evaporation Rate: Not available

Flash Point (°C): Not applicable

Upper Explosive Limit (%): Not applicable

Decomposition Temp (°C): Not available

Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

Product is considered stable and hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result. The material may produce foreign body irritation in certain individuals.

continued...

EPIREZ EPOXY ANTI-SLIP FLOORING AGGREGATE [SIL-CARB]

Chemwatch Material Safety Data Sheet
Issue Date: 26-Apr-2006
C317SC

CHEMWATCH 8013-72
CD 2006/2 Page 7 of 8

Section 11 - TOXICOLOGICAL INFORMATION

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

INHALED

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung. Prime symptom is breathlessness; lung shadows show on X-ray. Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
 - Consult State Land Waste Management Authority for disposal.
 - Bury residue in an authorised landfill.
 - Recycle containers if possible, or dispose of in an authorised landfill.
-

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM

None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN,IATA,IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

None

continued...

EPIREZ EPOXY ANTI-SLIP FLOORING AGGREGATE [SIL-CARB]

Chemwatch Material Safety Data Sheet

Issue Date: 26-Apr-2006

C317SC

CHEMWATCH 8013-72

CD 2006/2 Page 8 of 8

Section 15 - REGULATORY INFORMATION

REGULATIONS

silicon carbide (CAS: 409-21-2) is found on the following regulatory lists;
Australia High Volume Industrial Chemical List (HVICL)
Australia Inventory of Chemical Substances (AICS)
OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 26-Apr-2006

Print Date: 13-Jul-2006