

GALMET
METAL PROTECTION
SAFETY DATA SHEET
RUSTPAINT (ALL COLOURS)

1 SUBSTANCE IDENTIFICATION AND COMPANY

PRODUCT NAME:	GALMET RUSTPAINT (ALL COLOURS)		
PRODUCT NO.	VARIOUS – Starting with letters GRP (not including aerosol products)		
USE:	Anticorrosive and decorative surface coating.		
SUPPLIER			
ITW POLYMERS & FLUIDS		Queensland Distributor	
100 HASSALL ST		INTERNATIONAL TRADERS pty ltd	
WETHERILL PARK 2164		ABN: 27100193619	
NEW SOUTH WALES		6/286 Evans Rd	
AUSTRALIA		Salisbury Q 4107	
T: 02 9757 8800		Ph: (07) 3272 9051	
F: 02 9757 3855		Fax: (07) 3272 9744	
EMERGENCY CONTACT:	T: 02 9757 8800		

2 HAZARDS IDENTIFICATION**HAZARDOUS SUBSTANCE. DANGEROUS GOODS**

(According to the criteria of the NOHSC and the ADG-6 code)

SIGNAL WORD(S)

F; Flammable, Xn; Harmful

RISK PHRASES

R10 Flammable.

R65 Harmful; May cause lung damage if swallowed.

SAFETY PHRASES

S2 Keep out of reach of children.

S23 Do not breathe vapour/spray.

S24/25 Avoid contact with skin & eyes.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

3 COMPOSITION / INFORMATION ON INGREDIENTS

Name	CAS-No.	Content	Classification
WHITE SPIRITS	64742-82-1	30 – < 60 %	Xn; R65
(Naphtha (petroleum), hydrodesulfurized heavy)			

4 FIRST AID MEASURES

GENERAL INFORMATION

Avoid contact with skin and eyes. Do not breathe vapour/spray. Show this safety data sheet to doctor in attendance. **INHALATION**
 Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.
 Contact physician if discomfort continues.

INGESTION

Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit does not enter the lungs. Get medical attention immediately!

RUSTPAINT SDS

SKIN CONTACT

Remove contaminated clothing. Wash skin thoroughly with soap and water for several minutes. Contact physician if irritation persists.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Contact physician if irritation persists.

5 FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA

Fire can be extinguished using: Alcohol resistant foam. Carbon Dioxide (CO₂). Dry Chemicals.

SPECIFIC HAZARDS

Flammable. Avoid breathing fire vapours. May travel considerable distance to source of ignition and flash back.

PROTECTIVE EQUIPMENT FOR FIREFIGHTERS

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SPECIAL FIRE FIGHTING PROCEDURES

Keep upwind to avoid fumes. Avoid water in straight hose stream; will scatter and spread fire. Cool containers exposed to flames with water until fire is out. Keep run-off water out of sewers and watercourses. Dike for water control.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Warn everybody of potential hazards and evacuate if necessary. Remove sources of ignition. Avoid inhalation of spray mist and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Absorb with sand or other inert absorbent. Transfer to a container for disposal. Containers with collected spillage must be properly labeled with correct contents and hazard symbol.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Take precautionary measures against static discharges. Storage tanks and other containers must be grounded. Do not smoke, use naked flames or other sources of ignition. Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.

STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place. Keep away from heat, sparks and open flame.

8 EXPOSURE CONTROL / PERSONAL PROTECTION

EXPOSURE STANDARDS

No exposure standards available for product.

Exposure standards for ingredients:

Name	TWA (LT) mg/m ³ 350	TWA (LT) ppm	STEL (ST) mg/m ³	STEL (ST) ppm	Source
Naphtha (petroleum), hydrodesulfurized heavy					Shell (2007)

RUSTPAINT SDS
PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash, quick drench.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

RESPIRATORY EQUIPMENT

Select and use respirators in accordance with AS/NZS 1715/1716.

In poorly ventilated areas use Type A organic vapour/gas filter with half face piece.

When sanding/grinding cured product the use of a P1 dust mask (disposable) or with replaceable filters is recommended.

Filter capacity and respirator type depends on exposure levels and type of contaminant. If entering spaces where the airborne concentration of a contaminant is unknown then the use of a Self-contained breathing apparatus (SCBA) with positive pressure air supply complying with AS/NZS 1715 / 1716, or any other acceptable International Standard is recommended.

HAND PROTECTION

Use protective gloves made of: Chemical resistant gloves: e.g. Nitrile.

EYE PROTECTION

Wear safety glasses or approved chemical safety goggles where eye exposure is reasonably probable.

SKIN PROTECTION

Barrier cream, Protection suit or overalls should be worn.

HYGIENE MEASURES

Keep away from food, drink and animal feeding stuffs. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving work place.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Liquid

COLOUR Various

ODOUR Solvent.

SOLUBILITY Not soluble in water

BOILING POINT (°C)	162 – 192	RELATIVE DENSITY	0.98 @ 20° C
VAPOUR DENSITY (air=1)	>1	VAPOUR PRESSURE	370 Pa @ 20°C
EVAPORATION RATE (butyl acetate =1)	0.140	VOLATILE BY VOL. (%)	45 %
pH-VALUE, CONC. SOLUTION	n/a	FLASH POINT (°C)	41
FLAMMABILITY LIMIT - LOWER(%)	0.7	AUTOIGNITION TEMP. (°C)	296°C
FLAMMABILITY LIMIT - UPPER(%)	6.5		

10 STABILITY & REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

MATERIALS TO AVOID

Strong oxidising agents.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire or high temperatures create: Nitrous gases (NO_x). Oxides of: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

Toxic Dose 1 - LD 50 (Oral Rat) >2000 mg/kg (oral rat) (WHITE SPIRITS) (Shell 2007)

INHALATION

Vapours may cause headache, fatigue, dizziness and nausea. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication.

INGESTION

Harmful, May cause lung damage if swallowed. May cause nausea, headache, dizziness and intoxication.

SKIN CONTACT

May cause moderate skin irritation. Prolonged, repeated expose may cause de-fatting of the skin which can lead to dermatitis.

EYE CONTACT

May irritation to eyes.

HEALTH WARNINGS

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

TARGET ORGANS

Central nervous system. Kidneys. Liver. Respiratory system, lungs. Skin.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

No data available, however expected to be harmful to the aquatic environment

MOBILITY

Do not discharge into drains, water courses or onto the ground.

DEGRADABILITY

No data available.

13 DISPOSAL INFORMATION**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

Paint left over paint onto newspaper, allow to dry and dispose in general waste. Empty steel can is recyclable. Check with your local council to see if they participate in a steel can recycling program.

14 TRANSPORT INFORMATION

ADG ROAD CLASS:	3
PROPER SHIPPING NAME:	PAINT
UN NO. ROAD	1263
ROAD PACK GR.	III

HAZCHEM CODE	3YE	IERG (HB76: 2004)	Guide 14
IMDG CLASS	3	UN NO. SEA	1993
IMDG PAGE	NO. 3	IMDG PACK GR.	III
EMS	F-E, S-E	MFAG	See Guide
MARINE POLLUTANT	No.		
UN NO. AIR	1993	ICAO CLASS	3
AIR PACK GR.	III		

15 REGULATORY INFORMATION

SUSDP S5

RISK PHRASES IN FULL

R10	Flammable
R65	Harmful; May cause lung damage if swallowed.

16 OTHER INFORMATION

* The solvent in this product contains less than 0.1 % benzene, classification and labelling as a carcinogen is not required.

Contact: Technical Manager (02 9757 8800)

REVISION DATE: 5 March 2007

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.